

PREFORMED STAINLESS STEEL STRAND

TYPE 302/304

Strand Diameter	Construction	Part Number	Fine Wire Diameter	Strand Weight Per 1000 Ft. Lbs.	Minimum Break Strength	Elongation %
3/16"	1 x 7	ASC 18817	.65	73	3,900	2.5
7/32"	1 x 7	ASC 21917	.072	106	6,300	2.5
1/4"	1 x 7	ASC 25017	.080	137	8,500	2.5
9/32"	1 x 7	ASC 28117	.093	176	10,700	2.5
5/16"	1 x 7	ASC 31317	.104	205	13,200	2.5
3/8"	1 x 7	ASC 37517	.120	300	18,000	2.5
7/16"	1 x 7	ASC 43817	.145	400	26,000	2.5
1/2"	1 x 7	ASC 50017	.165	562	33,700	2.5
9/16"	1 x 7	ASC 56617	.188	728	43,750	2.5
5/8"	1 x 7	ASC 62517	.207	871	50,250	2.5
3/8"	1 x 19	ASC 37519	.072	294	17,500	2.5
7/16"	1 x 19	ASC 43819	.087	410	24,000	2.5
1/2"	1 x 19	ASC 50019	.100	521	33,300	2.5
9/16"	1 x 19	ASC 56319	.113	670	42,125	2.5
5/8"	1 x 19	ASC 62519	.125	855	50,250	2.5
3/4"	1 x 19	ASC 75019	.150	1253	72,875	2.5
7/8"	1 x 19	ASC 87819	.177	1715	99,625	2.5
1"	1 x 19	ASC 90119	.200	2250	130,650	2.5
1"	1 x 37	ASC 90137	.143	2200	128,375	2.5
1 1/8"	1 x 37	ASC 101837	.161	2947	163,500	2.5
1 1/4"	1 x 37	ASC 111437	.179	3555	202,750	2.5