

PREFORMED STAINLESS STEEL STRAND

TYPE 316

Strand Diameter	Construction	Part Number	Fine Wire Diameter	Strand Weight Per 1000 Ft. Lbs.	Minimum Break Strength	Elongation %
3/16"	1 x 7	ASZ 18817	.065	73	3,430	3
7/32"	1 x 7	ASZ 21917	.072	106	5,700	3
1/4"	1 x 7	ASZ 25017	.080	137	7,650	3
9/32"	1 x 7	ASZ 28117	.093	176	9,650	3
5/16"	1 x 7	ASZ 31317	.104	205	11,900	3
3/8"	1 x 7	ASZ 37517	.120	300	16,200	3
7/16"	1 x 7	ASZ 43817	.145	400	23,400	3
1/2"	1 x 7	ASZ 50017	.165	562	30,200	3
9/16"	1 x 7	ASZ 56617	.188	728	39,620	3
5/8"	1 x 7	ASZ 62517	.207	871	48,000	3
3/8"	1 x 19	ASZ 37519	.072	294	15,800	3
7/16"	1 x 19	ASZ 43819	.087	410	21,000	3
1/2"	1 x 19	ASZ 50019	.100	521	28,500	3
9/16"	1 x 19	ASZ 56319	.113	670	35,400	3
5/8"	1 x 19	ASZ 62519	.125	855	45,600	3
3/4"	1 x 19	ASZ 75019	.150	1253	66,000	3
7/8"	1 x 19	ASZ 87819	.177	1715	90,220	3
1"	1 x 19	ASZ 90119	.200	2250	116,250	3
1"	1 x 37	ASZ 90137	.143	2200	115,295	3
1 1/8"	1 x 37	ASZ 101837	.161	2947	143,230	3
1 1/4"	1 x 37	ASZ 111437	.179	3555	183,000	3