

# Strand-Eye Anchor Rods

TYPE 316 Stainless Steel

Rolled threads are furnished on all rods up to and including 3/4" diameter. 1" and larger have cut threads. Length of thread –3-1/2". Manufactured to ANSI Standards.



Figure 2-6



Figure 2-7



Figure 2-8

STOCK NO.	LGTH FT.	APPROX. WT. LBS. PER 100 PCS.	STOCK NO.	LGTH FT.	APPROX. WT. LBS. PER 100 PCS.	STOCK NO.	LGTH FT.	APPROX. WT. LBS. PER 100 PCS.
<b>SINGLE EYE-Figure 2-6</b>			<b>DOUBLE EYE-Figure 2-7</b>			<b>TRIPLE EYE-Figure 2-8</b>		
<b>1/2" Diameter Rod --- Minimum Strength 10,000 Lbs.</b>								
AR1-125316	5	300	-	-	-	-	-	-
AR1-126316	6	450	-	-	-	-	-	-
AR1-127316	7	500	-	-	-	-	-	-
<b>5/8" Diameter Rod --- Minimum Strength 16,000 Lbs.</b>								
AR1-585316	5	590	-	-	-	-	-	-
AR1-586316	6	664	AR2-586316	6	690	-	-	-
AR1-587316	7	766	AR2-587316	7	765	-	-	-
AR1-588316	8	830	AR2-588316	8	840	-	-	-
<b>3/4" Diameter Rod --- Minimum Strength 23,000 Lbs.</b>								
AR1-346316	6	960	AR2-346316	6	970	-	-	-
AR1-347316	7	1230	AR2-347316	7	1130	AR3-347316	7	1130
AR1-348316	8	1245	AR2-348316	8	1403	AR3-348316	8	1255
-	-	-	AR2-349316	9	1460	AR3-349316	9	1460
-	-	-	AR2-3410316	10	1520	-	-	-
<b>1" Diameter Rod --- Minimum Strength 36,000 Lbs.</b>								
AR1-108316	8	2300	AR2-108316	8	2310	AR3-108316	8	2310
-	-	-	AR2-109316	9	2530	-	-	-
AR1-1010316	10	2600	AR2-1010316	10	2895	AR3-1010316	10	2895
<b>1 1/4" Diameter Rod --- Minimum Strength 58,000 Lbs.</b>								
-	-	-	AR2-11410316	10	4400	AR3-11410316	10	4620