



1x19 PREFORMED GALVANIZED STRAND NON-FLEXIBLE

MILITARY SPECIFICATION

Mil-W-87161. September 1982. Wire Strand. Non-Flexible for Aircraft Application Type II. Composition A: Carbon Steel, Zinc Coated. Construction 1 Right Lay: Construction 2 - Left Lay, Superseding Mil-W-5693. December 1965: Mil-W-6940. August 1969.

COMMERCIAL GRADE

Specification SD 118. Oil Free - Dry Condition

CODE	100 FT. IN LBS.	STRENGTH IN LBS.	PART NUMBER	DIAM. IN INCHES
○	.25	185	GC 03119	1/32
△	.55	375	GF 04719	3/64
○	.55	375	GC 04719	3/64
△	.85	500	GF 06319	1/16
○	.85	500	GF 06319	1/16
△	1.4	800	GF 07819	5/64
○	1.4	800	GC 07819	5/64
△	2.0	1,200	GF 09419	3/32
○	2.0	1,200	GC 09419	3/32
△	2.7	1,600	GF 10919	7/64
○	2.7	1,600	GC 10919	7/64
△	3.5	2,100	GF 12519	1/8
○	3.5	2,100	GC 12519	1/8
△	5.5	3,300	GF 15619	5/32
○	5.5	3,300	GC 15619	5/32
△	7.7	4,700	GF 18819	3/16
○	7.7	4,700	GC 18819	3/16
△	10.2	6,300	GF 21919	7/32
○	10.2	6,300	GC 21919	7/32
△	13.5	8,200	GF 25019	1/4
○	13.5	8,200	GC 25019	1/4
△	17.0	10,300	GF 29119	9/32
○	17.0	10,300	GC 29119	9/32
△	21.0	12,500	GF 31319	5/16
○	21.0	12,500	GC 31319	5/16
△	30.1	17,500	GF 37519	3/8
○	30.1	17,500	GC 37519	3/8