



7x19 PREFORMED GALVANIZED AIRCRAFT CABLE

MILITARY SPECIFICATION

Mil-W-83420. Latest Amendment. Wire Rope. Flexible for Aircraft Control. Type-I - Non-Jacketed Wire Rope. Composition A. Carbon Steel, Zinc Coated, or Zinc and Tin Coated.

COMMERCIAL GRADE

Specification SD 118. Oil Free - Dry condition.

CODE	APPROX. WEIGHT PER 100 FT.	MINIMUM BREAK STRENGTH IN LBS.	PART NUMBER	DIAM. IN INCHES
△	.75	480	GF 06379	1/16
○	.75	480	GC 06379	1/16
△	1.7	1,000	GF 09479	3/32
○	1.7	1,000	GC 09479	3/32
△	2.9	2,000	GF 12579	1/8
○	2.9	2,000	GC 12579	1/8
△	4.5	2,800	GF 15679	5/32
○	4.5	2,800	GC 15679	5/32
△	6.5	4,200	GF 18879	3/16
○	6.5	4,200	GC 18879	3/16
△	8.6	5,600	GF 21979	7/32
○	8.6	5,600	GC 21979	7/32
△	11.0	7,000	GF 25079	1/4
○	11.0	7,000	GC 25079	1/4
△	13.9	8,000	GF 28179	9/32
△	17.3	9,800	GF 31379	5/16
○	17.3	9,800	GC 31379	5/16
△	24.3	14,400	GF 37579	3/8
○	24.3	14,400	GC 37579	3/8

McDONNELL DOUGLAS SPECS.

AdSCO is a qualified producer of the listed McDonnell Douglas Aircraft Corporation wire rope products.

DMS 2187-1-A	5/16"	7x31	IWRC	Galvanized
DMS 2187-1-A	3/8"	7x31	IWRC	Galvanized
DMS 2192-1-A	3/16"	6x31	IWRC	Galvanized
DMS 2192-1-A	1/4"	6x31	IWRC	Galvanized

Call for price and delivery