


# 1x19 PREFORMED STAINLESS STEEL STRAND TYPE 316 (EXTRA CORROSION-RESISTANT)

WEIGHT PER 100 FT.	MINIMUM BREAK STRENGTH IN LBS.	PART NUMBER	DIAM IN INCHES
3.5	1,780	SZ 12519*	1/8
5.5	2,800	SZ 15619*	5/32
7.7	4,000	SZ 18819*	3/16
10.2	5,350	SZ 21919	7/32
13.5	6,900	SZ 25019*	1/4
21.0	10,600	SZ 31319	5/16
30.0	14,800	SZ 37519*	3/8
41.0	20,000	SZ 43819	7/16
52.1	27,000	SZ 50019	1/2
67.0	32,400	SZ 56219	9/16
85.5	42,000	SZ 62519	5/8



# 1x7 PREFORMED STAINLESS STEEL CABLE TYPE 316 (EXTRA CORROSION-RESISTANT) NON-FLEXIBLE

APPROX. WEIGHT 100 FT. IN LBS.	MINIMUM BREAK STRENGTH IN LBS.	PART NUMBER	DIAM. IN INCHES
10.6	5,700	SZ 21917	7/32
13.7	7,650	SZ 25017	1/4
17.6	9,650	SZ 28117	9/32
20.5	11,900	SZ 31317	5/16
30.0	16,200	SZ 37517	3/8
45.0	23,400	SZ 43817	7/16
56.0	30,200	SZ 50017	1/2