

1x7

STAINLESS STEEL MINIATURE STRAND NYLON JACKETED TYPE 302/304

COMMERCIAL GRADE

Specification SD 119. Nylon Jacketed Mechanical Strand and Cable.

| CODE | APPROX. WEIGHT PER 100 FT. | MINIMUM BREAK STRENGTH IN LBS. | PART NUMBER | DIAM IN INCHES |
|------|----------------------------|--------------------------------|-------------|----------------|
| ○ | .11 | 80 | SC 0211701 | .021 - .040 |
| ○ | .14 | 100 | SC 0241701 | .024 - .040 |
| ○ | .19 | 125 | SC 0271701 | .027 - .040 |
| ○ | .25 | 150 | SC 0301701 | .030 - .050 |
| ○ | .33 | 210 | SC 0361701 | .036 - .050 |
| ○ | .45 | 290 | SC 0421701 | .042 - .060 |



3x7

STAINLESS STEEL MINIATURE STRAND NYLON JACKETED TYPE 302/304


MILITARY SPECIFICATION

Mil-W-83420. Latest Amendment. Wire Rope. Flexible for Aircraft Control. Type-II - Jacketed Wire Rope. Composition B. Corrosion-Resistant Steel.

COMMERCIAL GRADE

Specification SD 119. Nylon Jacketed Mechanical Strand and Cable.

| CODE | APPROX. WEIGHT PER 100 FT. IN LBS. | MINIMUM BREAK STRENGTH IN LBS. | PART NUMBER | DIAM IN INCHES |
|------|------------------------------------|--------------------------------|-------------|----------------|
| △ | .22 | 110 | SF 0313701 | 1/32-3/64 |
| ○ | .22 | 110 | SC 0313702 | 1/32-3/64 |
| △ | .34 | 230 | SF 0473701 | 3/64-1/16 |
| ○ | .34 | 230 | SC 0473702 | 3/64-1/16 |



7x7

TYPE 302/304 STAINLESS STEEL AIRCRAFT GROUNDING CABLE JACKETED WITH LOLON "M" MAXIMUM ELECTRICAL RESISTANCE: 10 OHMS PER 75 FEET

COMMERCIAL GRADE

Meets latest commercial specifications.

| CODE | APPROX. WEIGHT PER 100 FT. IN LBS. | MINIMUM BREAK STRENGTH IN LBS. | PART NUMBER | DIAM IN INCHES |
|------|------------------------------------|--------------------------------|-------------|----------------|
| ○ | 2.2 | 920 | SC 0947724 | 3/32-5/32 |