




# 6x42 NON-PREFORMED STAINLESS STEEL WIRE ROPE TYPE 302/304

FEDERAL SPECIFICATION

RR-W-410, Latest Amendment, Type III, Class 6

WEIGHT PER 100 FT.	MINIMUM BREAK STRENGTH IN LBS.	PART NUMBER	DIAM IN INCHES
1.8	700	SR 12564	1/8
4	1,600	SR 18864	3/16
7	3,200	SR 25064	1/4
11	4,900	SR 31364	5/16
16	6,900	SR 37564	3/8
21	9,300	SR 43864	7/16
28	12,000	SR 50064	1/2
35	15,000	SR 56264	9/16
43	18,400	SR 62564	5/8
61	26,200	SR 75064	3/4
82	35,600	SR 87564	7/8
108	46,500	SR 10064	1
136	59,000	SR 11264	1-1/8
169	72,500	SR 12564	1-1/4



# 19x7 PREFORMED STAINLESS STEEL WIRE ROPE TYPE 302/304

△ MILITARY SPECIFICATION

Mil-W-883140, April 1969, Wire Rope: Steel Preformed, Nonrotating, for Aircraft Rescue Hoist and Cargo Handling, Type I.

CODE	APPROX. WEIGHT 100 FT.	MINIMUM BREAK STRENGTH IN LBS.	PART NUMBER	DIAM IN INCHES
△	4.5	2,160	SF 15697	5/32
△	6.5	3,330	SF 18897	3/16
△	8.6	4,500	SF 21997	7/32
△	11	5,760	SF 25097	1/4
△	17.3	8,100	SF 31397	5/16
△	24.3	10,800	SF 37597	3/8
△	45.8	20,520	SF 50097	1/2
△	71.5	31,500	SF 62597	5/8