

# 6x19 CLASS PREFORMED STAINLESS STEEL WIRE ROPE I.W.R.C. - TYPE 316 (EXTRA CORROSION-RESISTANT)


COMMERCIAL GRADE

APPROX. WEIGHT PER 100 FT.	MINIMUM BREAK STRENGTH IN LBS.	PART NUMBER	DIAM. IN INCHES
35.6	15,000	SZ 4362506	7/16
45.8	19,300	SZ 5062506	1/2
59	24,300	SZ 5662506	9/16
71.5	29,800	SZ 6262506	5/8
92.2	50,000	SZ 7562506	3/4
143	58,000	SZ 8762506	7/8
187	80,000	SZ 1062506	1
240	90,440	SZ 1162506	1-1/8
290	110,000	SZ 1262506	1-1/4



# 7x7 PREFORMED STAINLESS STEEL CABLE TYPE 316 (EXTRA CORROSION-RESISTANT)

APPROX. WEIGHT 100 FT. IN LBS.	MINIMUM BREAK STRENGTH IN LBS.	PART NUMBER	DIA. IN INCHES
.75	360	SZ 06377	1/16
1.6	700	SZ 09477	3/32
2.85	1,360	SZ 12577	1/8



# 7x19 PREFORMED STAINLESS STEEL CABLE CABLE TYPE 316 (EXTRA CORROSION-RESISTANT)

APPROX. WEIGHT PER 100 FT.	MINIMUM BREAK STRENGTH IN LBS.	PART NUMBER	DIAM IN INCHES
2.9	1,300	SZ 12579	1/8
4.5	2,000	SZ 15679	5/32
6.5	2,900	SZ 18879	3/16
11.0	4,900	SZ 25079	1/2
17.3	7,600	SZ 31379	5/16
24.3	11,000	SZ 37579	3/8