




7x7

PREFORMED STAINLESS STEEL WIRE CABLE TYPE 305 NON-MAGNETIC


APPROX. WEIGHT PER 100 FT.	MINIMUM BREAK STRENGTH IN LBS.	PART NUMBER	DIAM IN INCHES
.75	360	SY 06377	1/16
1.6	700	SY 09477	3/32



7x19

PREFORMED STAINLESS STEEL WIRE CABLE TYPE 305 NON-MAGNETIC

APPROX. WEIGHT PER 100 FT.	MINIMUM BREAK STRENGTH IN LBS.	PART NUMBER	DIAM IN INCHES
2.9	1,300	SY 12579	1/8
4.5	2,000	SY 15679	5/32
6.5	2,900	SY 18879	3/16
11.0	4,900	SY 25079	1/4
17.3	7,600	SY 31379	5/16
24.3	11,000	SY 37579	3/8



6x19 CLASS

PREFORMED STAINLESS STEEL WIRE ROPE I.W.R.C. TYPE 305 NON-MAGNETIC

APPROX. WEIGHT PER 100 FT.	MINIMUM BREAK STRENGTH IN LBS.	PART NUMBER	DIAM IN INCHES
35.6	14,900	SY 4362506	7/16
45.8	19,300	SY 5062506	1/2
59.0	24,300	SY 5662506	9/16
71.5	30,100	SY 6262506	5/8
105.2	42,900	SY 7562506	3/4
143	58,000	SY 8762506	7/8
187	75,200	SY 1062506	1